



# R L LAUGHLIN VIASAT-100

Satellite Monitoring with Universal Protocol Compatibility

## Overview

The ViaSat-100 is a Class I Div 2 satellite transceiver that delivers monitoring and control capabilities for industrial devices and assets in remote areas.

ViaSat-100's two-way satellite connectivity is ideal for remotely monitoring and controlling assets such as pumpjacks, pipelines, tanks, pressure transmitters, flow meters, pumps, generators, and more .

R L Laughlin provides a complete, end-to-end satellite monitoring solution with the ViaSat-100, delivering sensors, communication hardware, and web SCADA access in one turnkey package.

## Specifications

-  Two-way satellite communication
-  Elevation angle: -5° to +90°
-  4 analog or digital in/out
-  RS-232 and RS-485
-  Compatible with Modbus, ROCTalk, ABB, and many devices and protocols
-  CE, FCC, IC, Anatel, RCM Mark, IEC 60945, C1D2, SRRC, IFT, ICASA, FFA
-  Input voltage: 9V to 32V
-  Operating temperature: -40°F to +185°F
-  4.96 inches x 4.96 inches x 1.93 inches

## Applications



Remote Pumpjack Monitoring



Remote Pipeline Monitoring



Remote Tank Monitoring

**And More . . .**